

3M™ Duct Tape 6969

Typical physical and performance characteristics include; thickness: 10.7 mil, adhesion to steel: 62 oz/in, tensile strength: 32 lb/in width, elongation at break: 16%, temperature use range: up to 200°F (93 °C) for up to one hour.



| Item Number | Description | Package Information | Size | Special Item Number | Case Qty | Color | UOM |
|-------------------|--|---------------------|------------|---------------------|----------|------------|-----|
| 000-21200-22773-8 | 3M™ Duct Tape 6969 Black, 48 mm x 54.8 m, 24 per case | 24 per case | 48mmx54.8m | 617-3 | 24 | Black | RL |
| 000-21200-22780-6 | 3M™ Duct Tape 6969 Olive, 48 mm x 54.8 m, 24 per case | 24 per case | 48mmx54.8m | 617-3 | 24 | Olive Drab | RL |
| 000-51131-06969-5 | 3M™ Duct Tape 6969 Silver, 48 mm x 54.8 m, 24 per case | 24 per case | 48mmx54.8m | 617-3 | 24 | Silver | RL |
| 000-21200-85635-8 | 3M™ Duct Tape 6969 Silver, 72 mm x 54.8 m, 12 per case | 12 per case | 72mmx54.8m | 617-3 | 12 | Silver | RL |

3M™ Duct Tape 3939

The all-around holding, splicing, masking, patching, sealing and seaming tape. Polyethylene coated cloth backing with rubber adhesive. High tack, conformability, strength and easy tear.



| Item Number | Description | Package Information | Size | Special Item Number | Case Qty | Color | UOM |
|-------------------|--|---------------------|------------|---------------------|----------|--------|-----|
| 000-21200-85561-0 | 3M™ Duct Tape 3939 Silver, 24 mm x 54.8 m, 36 per case | 36/Cs | 24mmx54.8m | 617-3 | 36 | Silver | RL |
| 000-51131-06975-6 | 3M™ Duct Tape 3939, 48 mm x 54.8 m, 24 per case | 24/Cs | 48mmx54.8m | 617-3 | 24 | Silver | RL |
| 000-21200-85562-7 | 3M™ Duct Tape 3939 Silver, 72 mm x 54.8 m, 12 per case | 12/Cs | 72mmx54.8m | 617-3 | 12 | Silver | RL |
| 000-21200-85563-4 | 3M™ Duct Tape 3939 Silver, 96 mm x 54.8 m, 12 per case | 12/Cs | 96mmx54.8m | 617-3 | 12 | Silver | RL |