

Scotch® Linerless Rubber Splicing Tape 130C

Scotch® Linerless Rubber Splicing Tape 130C is a highly conformable, linerless Ethylene Propylene Rubber (EPR), high-voltage insulating tape that provides excellent thermal dissipation of splice heat. Scotch® Splicing Tape 130C meets industry specifications and has excellent physical and electrical properties, which help provide immediate moisture seal and void-free buildups. Scotch® Splicing Tape 130C is rated up to 194°F (90°C) continuous operating temperatures and short-term 266°F (130°C) overload service. This product can be used for low and high-voltage (through 69 kV) applications. This tape should be applied like any rubber tape—that is, the side of the tape wrapped inside the roll should be applied outside on the splice (tacky side up). This will help prevent the roll from getting progressively further away from the work area.

| | |
|------------------------------------|---|
| Liner/Linerless | Linerless |
| Material | Self-fusing Ethylene Propylene Rubber (EPR) |
| Tape Grade | Premium |
| Tape Type | Insulating and Splicing |
| Operating Temperature | Up to 194°F (90°C) |
| Short Term Overload Service | 266°F (130°C) |
| RoHS 2011/65/EU | Yes |
| Specifications | ASTM D-4388 type 1, 2 & 3; HH-I-553C |
| Country of Origin |  |



| Order No. | UPC | Color | Length | Width | Thickness | Elongation | Breaking Strength | Rolls per Carton | Rolls per Case |
|-----------------|--------------|-------|--------|-------|-----------|------------|-------------------|------------------|----------------|
| 130C-3/4X30FT | 054007-41717 | Black | 30' | 0.75" | 30 mil | 850% | 7.5 lbs/in | 1 | 24 |
| 130C-1X10FT | 054007-41751 | Black | 10' | 1.00" | 30 mil | 850% | 7.5 lbs/in | 1 | 24 |
| 130C-1X15FT | 054007-41752 | Black | 15' | 1.00" | 30 mil | 850% | 7.5 lbs/in | 1 | 24 |
| 130C-1X30FT | 054007-41753 | Black | 30' | 1.00" | 30 mil | 850% | 7.5 lbs/in | 1 | 24 |
| 130C-1-1/2X30FT | 054007-41718 | Black | 30' | 1.50" | 30 mil | 850% | 7.5 lbs/in | 1 | 12 |
| 130C-2X30FT | 054007-41754 | Black | 30' | 2.00" | 30 mil | 850% | 7.5 lbs/in | 1 | 12 |