





Shown actual size: Skylark dimmer and 1-gang Claro wallplate in White (WH).

### Product family features


- Rocker switch returns light to light level indicated by slider on preset dimmers
- Slide up to brighten, down to dim
- C•L® and eco-dim® models available
- Coordinating Claro® and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates, see p. 237

### Control types


 Single-pole (one location)


 3-way or 4-way (two or more locations)


### Direct load type compatibility


 Incandescent/halogen lighting

 Dimmable CFL/LED lighting (screw-base)


 Magnetic low-voltage lighting

 Electronic low-voltage lighting


 Fluorescent lighting

 LED lighting

 Ceiling fans

 Ceiling fan/lights

### Load type requiring load interface

 Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information, see pp. 255–259.

**Available finishes**

Use **BOLD** color code in model number (Example: S-600P-**GR**)

Gloss finishes\*



**WH**  
White



**LA**  
Light Almond



**AL**  
Almond



**IV**  
Ivory



**GR**  
Gray



**BR**  
Brown



**BL**  
Black

Metal finish wallplates\*\*\*



**SS**  
Stainless Steel

\* Coordinating wallplates only available separately. For wallplate information, see p. 236.

\*\* Stainless Steel wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) control. For wallplate information, see p. 236

## Dimmers with on/off switch



- Rocker switch returns light to light level indicated by slider
- Slide up to brighten, down to dim
- C•L® dimmer provides reliable dimming of dimmable CFL/LEDs, as well as halogens and incandescents
- eco-dim® model guarantees at least 15% energy savings and triples lamp life compared to a standard switch\*

### Incandescent/halogen dimmer

### / Dimmable CFL/LED (screw-base) dimmer

#### C•L dimmer with on/off switch

3-way/single-pole SCL-153P-**XX**<sup>1</sup>  
120V 600W (Inc) 150W (CFL/LED)

Visit [www.lutron.com/dimcflled](http://www.lutron.com/dimcflled) for an approved list of dimmable CFLs/LED bulbs, and how to calculate wattage when mixing lamp types.

Adjustable low-end trim.

### Incandescent/halogen dimmers

#### Dimmers with on/off switch

Single-pole 120V 600W	S-600P- <b>XX</b> <sup>1</sup>
Single-pole 120V 1000W	S-10P- <b>XX</b> <sup>1</sup>
3-way 120V 600W	S-603P- <b>XX</b> <sup>1</sup>
3-way 120V 1000W	S-103P- <b>XX</b> <sup>1</sup>

#### eco-dim dimmer with on/off switch

3-way/single-pole 120V 600W	S-603PG- <b>XX</b> <sup>2</sup>
--------------------------------	---------------------------------

### Magnetic low-voltage dimmers

#### Dimmers with on/off switch

Single-pole 120V 600VA (450W)	SLV-600P- <b>XX</b> <sup>1</sup>
3-way 120V 600VA (450W)	SLV-603P- <b>XX</b> <sup>1</sup>

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

**XX**<sup>1</sup>: Gloss color codes, see p. 103

**XX**<sup>2</sup>: Available in White (WH), Ivory (IV), Almond (AL) and Light Almond (LA)

Wallplates not included. Order separately, see p. 236

All models must be derated if ganged unless otherwise noted, see pp. 250–252 and 254.

\* Maximum light output of 85% guarantees 15% energy savings over standard switches